



UCY ENERGY

Saving future for the next generation!

WWW.UCY-ENERGY.COM

A division of
UCY business services & trading GmbH

Oil-, Gas- & Coal-Supply +++ Energy Trading +++ Refineries +++ Power Plants

UCY ENERGY, Am Villepohl 4, D-53347 Alfter, Germany

Alfter, 23.05.2011 13:25

Contact person: Thilo Schneider

Office Phone: +39 01 65 / 4 30 81

Cellular Phone: +49 1 63 / 81 41 78 - 9

E-mail: thilo.schneider@ucy-energy.com

UCY ENGERY
UCY business services
& trading GmbH

Global Head Office
Bonn (GHOB):
Am Villepohl 4
D-53347 Alfter / Bonn
Germany
Phone:
+49 / 2 28 / 24 28 - 7 32
Facsimile:
+49 / 2 28 / 24 28 - 7 31
E-Mail:
Bonn@ucy-energy.com

Central Project Office
Essen (CPOE):
Planckstrasse 83
D-45147 Essen
Germany
Phone:
+49 / 2 01 / 81 41 78 - 92
Facsimile:
+49 / 2 01 / 81 41 78 - 96
E-mail:
Essen@ucy-energy.com

Energy Sales /
Communication
Kenzingen (ESCK):
Herrenbergstrasse 3
D-79341 Kenzingen
Germany
Phone:
+49 / 76 44 / 92 90 - 89
Facsimile:
+49 / 76 44 / 92 90 - 94
E-mail:
Kenzingen@
ucy-energy.com

Bank:
VR-Bank Bonn eG
Bank Code No. (BLZ):
381 602 20
Account No.:
630 712 40 15
SWIFT / BIC:
GENO DE D1 HBO
IBAN:
DE 24 381 602 20 630
712 40 15

Tax number:
222 / 5719 / 235
USt.Id.Nr. (Value added
tax identification
number):
DE 2 39 98 81 54

Register court:
Amtsgericht Bonn
Register number:
HRB 13459

Chief Executive Officer:
Thilo Schneider

General e-mail:
info@ucy-energy.com
Personal e-mail:
Name.surname@
ucy-energy.com

Homepage:
www.ucy-energy.com

UCY ENERGY ® is a
trademark of UCY
business services and
trading GmbH, Alfter,
Germany.

RECYCLED FUEL OIL

Physical properties

Liquid mixture of several vegetable oils 10% and mineral oil 90%. No smell characteristic. not mixable in water, how ever, mixable in some organic solvents

Specifications

Characteristics	Method	Results
Sulfur	ASTM D 129	0,90 % (M/M)
Water, % (m/m) max	ASTM D 95	1,0% (v / v)
Density (15°C)	NP -1695	0,882 g / cm3
Sediments	ASTM D 893	0,81 % (c / v)
Calorific value, superior	ASTM D 240	10.568 Kcal / Kg
Calorific value, inferior	ASTM D 240	10.256 Kcal / Kg
Inflamation point	ASTM D93 – 2a	> 40°C

THIS OIL IS NOT FOR BIODIESEL PRODUCTION !

UN CODE : 1993.

**Nota: This product is more ecological than regular fuel-oil
The content of sulfur and ash are more limited.**

Application : Fuel oil for boilers and power plant inceneration.

Samples are available for personal analysis before use .