

www.ucy-energy.com

PSF-CI10 fine **Product Data Sheet** Item number: 60-034

General Information

Sulphate of Potash 50 (+45) 50 % K₂O, water-soluble potassium oxide (=41.5 % K) 45 % SO₃, water-soluble sulphur trioxide (=18 % S)

PSF-Cl10 fine is a concentrated potassium and sulphur fertilizer used for the manufacture of compound fertilizers and also suitable for straight manual application. It is particular recommended to increase yield and quality of tobacco and other chloride sensitive crops e.g. vegetables and fruits. Moreover **PSD-CL10 fine** is the preferred form of potassium for salt affected soils because it is virtually free of chloride and has a low salt index.

The product is made from crude potassium salt of natural origin and is permitted for use in organic farming according to the Regulations (EC) No 834 / 2007 and (EC) No 889 / 2008.

Chemical Analysis

Parameter	Unit	Typical value
Potassium Sulphate (K ₂ SO ₄)	%	93
Other Sulphates (MgSO ₄ , CaSO ₄)	%	4.1
Chlorides (KCl, NaCl)	%	1.7
Others, mainly Water of Crystallization	%	1
Moisture	%	0.2

Granulometry

Parameter		Unit	Typical value
Tyler Mesh +20	> 0.85 mm	%	2
Tyler Mesh 32 – 20	0.5 – 0.85 mm	%	3
Tyler Mesh 60 – 32	0.25 – 0.5 mm	%	12
Tyler Mesh 100 – 60	0.15 – 0.25 mm	%	25
Tyler Mesh 170 – 100	0.09 – 0.15 mm	%	31
Tyler Mesh -170	< 0.09	%	27
SGN		%	13

- continue on page 2 -

UCY ENERGY UCY business services & trading GmbH Am Villepohl 4 D-53347 Alfter Germany Phone: +49 / 2 28 / 24 28 - 7 32 International Office: +49 / 2 28 / 30 41 - 37 00 Facsimile: +49 / 2 28 / 24 28 - 7 31 E-mail: info@ucy-energy.com www.ucy-energy.com Register number: HRB 13459 Register court: Bonn Tax number: 222/5719/235 VAT-ID: DE 2 39 98 81 54 Managing Director: Thilo Schneider



www.ucy-energy.com

- page 2 -

Storage

Parameter	Unit	Typical value
Bulk Density	kg∕m³	approx. 1,350
Bulk Density	lbs / ft³	approx. 84
Bulk Density (packed)	kg∕m³	approx. 1,450
Bulk Density (packed)	lbs / ft³	approx. 91
Angle of Repose	0	approx. 33

The product is to be kept dry and covered with a plastic tarpaulin to protect from moisture. Where bulk product is stored, steel joists and columns should be protected from corrosion, as well as the floor and the walls should be furnished with a protective coating. Wooden walls and roof girders have proved to be particularly durable.

Phone: +49 / 2 28 / 24 28 - 7 32 International Office: +49 / 2 28 / 30 41 - 37 00 Facsimile: +49 / 2 28 / 24 28 - 7 31 E-mail: <u>info@ucy-energy.com</u> <u>www.ucy-energy.com</u> Register number: HRB 13459 Register court: Bonn Tax number: 222/5719/235 VAT-ID: DE 2 39 98 81 54 Managing Director: Thilo Schneider