## **UCY ENERGY**

### UCY business services & trading (Germany) GmbH



www.ucy-energy.com

# PSF-CI10-GR Product Data Sheet

Item number: 60-035

#### **General Information**

Sulphate of Potash 50 (+45) 50 %  $K_2O$ , water-soluble potassium oxide (=41.5 % K) 45 %  $SO_3$ , water-soluble sulphur trioxide (=18 % S)

**PSF-Cl10-GR** is a concentrated potassium and sulphur fertilizer perfectly suited to mechanized spreading and bulk blending as well as to straight manual application. It is particular recommended to increase yield and quality of chloride sensitive crops e.g. vegetables and fruits, grapes and tobacco. Moreover **PSF-Cl10-GR** is the preferred form of potassium for salt affected soils because it is virtually free of chloride and has a low salt index.

The product is made from crude potassium salt of natural origin and is permitted for use in organic farming according to the Regulations (EC) No 834 / 2007 and (EC) No 889 / 2008.

#### **Chemical Analysis**

Parameter	Unit	Typical value
Potassium Sulphate (K <sub>2</sub> SO <sub>4</sub> )	%	93
Other Sulphates (MgSO <sub>4</sub> , CaSO <sub>4</sub> )	%	3
Chlorides (KCl, NaCl)	%	1.4
Others, mainly Water of Crystallization	%	2.6

#### **Granulometry**

Parameter		Unit	Typical value
Tyler Mesh +5	> 4 mm	%	3
Tyler Mesh 9 – 5	2 – 4 mm	%	89
Tyler Mesh -9	< 2 mm	%	8
SGN		%	280

- continue on page 2 -

E-mail: <u>info@ucy-energy.com</u> <u>www.ucy-energy.com</u> Register number: HRB 13459 Register court: Bonn Tax number: 222/5719/235 VAT-ID: DE 2 39 98 81 54

Managing Director: Thilo Schneider

## **UCY ENERGY**

## UCY business services & trading (Germany) GmbH



www.ucy-energy.com

- page 2 -

## **Storage**

Parameter	Unit	Typical value
Bulk Density	$kg / m^3$	approx. 1,250
Bulk Density	lbs / ft³	approx. 78
Bulk Density (packed)	$kg / m^3$	approx. 1,300
Bulk Density (packed)	lbs / ft³	approx. 81
Angle of Repose	o	approx. 38

The product is to be kept dry and covered with a plastic tarpaulin to protect from moisture. Where bulk product is stored, steel joists and columns should be protected from corrosion, as well as the floor and the walls should be furnished with a protective coating. Wooden walls and roof girders have proved to be particularly durable.

E-mail: info@ucy-energy.com VAT-ID: DE 2 39 98 81 54
www.ucy-energy.com Managing Director: Thilo Schneider

Register number: HRB 13459

Tax number: 222/5719/235

Register court: Bonn