UCY ENERGY

UCY business services & trading (Germany) GmbH



www.ucy-energy.com

UCY25-CE Product Datasheet

Item number: 10-032

General Information

DescriptionBlend of TOFA and DTO with a high level of DTO

Uses Alkyd resins, industrial oils, soaps, drilling fluids, surfactants and

bitumen emulsions

CAS 8002-26-4 / 61790-12-3 EINECS 232-304-6 / 263-107-2

Typical properties

Analysis	Value
Acid value	187
Gardner color	max. 7
Rosin acids (%)	25
Density at 20 °C (g / ml)	0.937
Oleic acid (%)	29
Linoleic acid (%)	20
Abietic acid (%)	7
Dehydroabietic acid (%)	3
Palmitic and stearic acids (%)	2
Unsaponifiable (%)	4

Transport

Handling & storage Under cover and at a temperature between 10 and 30 °C,

containers must be kept closed, this product is sensitive to

crystallization

Stability Stability of about 6 months in standard conditions

Packaging Available in drums of 190 kg net weight on pallets of 760 kg net, in

plastic containers of 900 kg and in bulk

Custom tariff 3803009000

Disclaimer:

The data herein are based on our knowledge about above product. They are without conditions and warranties, expressed or implied regarding the uses of the product.

UCY ENERGY UCY business services & trading GmbH Am Villepohl 4

D-53347 Alfter Germany Phone: +49 / 2 28 / 24 28 - 7 32 International Office: +39 / 01 65 / 4 30 81 Facsimile: +49 / 2 28 / 24 28 - 7 31

E-mail: <u>info@ucy-energy.com</u> <u>www.ucy-energy.com</u> Register number: HRB 13459 Register court: Bonn Tax number: 222/5719/235 VAT-ID: DE 2 39 98 81 54

Managing Director: Thilo Schneider